

ATF



FULL SYNTHETIC MULTI VEHICLE

A 100% synthetic blend multi-purpose transmission fluid for use in automatic gear boxes where Dexron III is quoted. Also suitable for certain power steering systems, torque converters, change-gearboxes, fluid clutches and non-complicated hydraulic systems. Petrocam ATF III has a sophisticated combination of high quality synthetic base oils and viscosity index that improves anti-oxidant, anti-wear, detergent and friction modifying additives.

SPECIFICATIONS DEXRON® III



APPLICATIONS

- Transmission fluid for use in automatic gear boxes and power steering systems
- Used in automatic gearboxes post 2005, in torque converters and numerous power steering systems in accordance with the specifications of the manufacturer.

KEY ADVANTAGE

- Excellent low temperature protection
- Compatible with wide range of seal materials
- Smooth transmission shift feel performance
- Excellent heat dissipation and foam suppression characteristics
- Outstanding friction durability performance over wide temperature
- Smoother transmission and synchronization

PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Density @ 15°C	ASTM D1298	kg/l	0.84-0.87
Color	ASTM D1500		Red
Viscosity @ 100°C	ASTM D445	cSt	6.7
Viscosity @ 40°C	ASTM D445	cSt	30
Viscosity Index (min)	ASTM D2270	-	Min 185
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-50
Fire Point	ASTM D92	°C	min 185
Brookfield Viscosity @ -10°C	ASTM D2983	cP	700
Brookfield Viscosity @ -20°C	ASTM D2983	cP	2,500
Brookfield Viscosity @ -30°C	ASTM D2983	cP	6,900
Copper Strip Corrosion	ASTM D130	-	1b
Foaming	ASTM D892	-	0/0/0

The values shown above are typical values at the date of publication. Petrocam Lubricants reserves the right to change these typical values without prior notice.

RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

PACKAGING

1 and 5 litre plastic bottles



ENERGY
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa
TEL: +27 11 656 0466
EMAIL: lubricants@petrocam.co.za

PETROCAM
— LUBRICANTS —

A Division Of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za