

# POWERBIKE

## SAE 30

MONO GRADE OIL WITH ADDED DILUENTS

A premium lubricant for high RPM **2-STROKE** engines that use a premix or injector lubrication system, enhanced oil film resistance and anti-wear protection from synthetic base stocks. Reduces ash and smoke to a minimum.

### SPECIFICATIONS

Meets and Exceeds  
API TC, JASO FC



### APPLICATIONS

- For use in motorcycles, snowmobiles and lean oil/fuel ratio chain saws or lawnmowers

### KEY ADVANTAGE

- Good wear protection
- Thermal and oxidation stability and deposit control
- Reduces pre-ignition
- Good corrosion protection properties

### PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Density @ 15°C	ASTM D1298	kg/l	0.859
Viscosity @ 100°C	ASTM D445	cSt	8.8
Viscosity @ 40°C	ASTM D445	cSt	53.8
Viscosity Index (min)	ASTM D2270	-	140
Pour Point	ASTM D97	°C	-39
Flash Point	ASTM D92	°C	245
Total Base Number (TBN)	ASTM D2896	mg KOH/g	1.5

The values shown above are typical values at the date of publication, Petrocam Lubricants reserves the right to change these typical values without prior notice.

### RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

### HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

### PACKAGING

1 Litre plastic bottles



ENERGY  
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa  
TEL: +27 11 656 0466  
EMAIL: lubricants@petrocam.co.za

**PETROCAM**  
— LUBRICANTS —

A Division Of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za