

TRANSGEAR

75W90

HIGH PRESSURE GEAR OIL

A fully synthetic universal all season gear lubricant formulated from synthetic base oils and an advanced additive system.

SPECIFICATIONS

Meets and Exceeds

API GL-4/GL-5

API MT-1

SAE J2360

MIL L 2105 D/PRF 2105 E

EATON Europe

MAN 341 Z2

MAN 341 S1

MB 235.8

MERITOR 0-76-N

SCANIA STO 1:0

VOLVO 97312

ZF TE-ML 02B

ZF TE-ML 12L

ZF TE-ML 12N

ZF TE-ML 19C



**ENERGY
IN MOTION**

www.petrocamlubricants.co.za

6 Western Service Road, Sandton, 2052, South Africa

TEL: +27 11 656 0466

EMAIL: lubricants@petrocam.co.za

**PETROCAM
— LUBRICANTS —**

A Division Of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za



APPLICATIONS

- Provides excellent low temperature fluidity for safe lubrication during very low temperature transmission and transaxle startup, and also maintains a thick protective oil film during extremely hot operating conditions
- Used in all synchronized and non-synchronized manual transmission types operating under heavy loads and at high speed in extremely low temperatures, where an API GL-4 and MT-1 oil is required.

KEY ADVANTAGE

- Superior wear protection
- Good thermal stability and resistance to high temperature oxidation
- Outstanding shear stability and frictional properties
- Excellent rust, staining, and corrosion protection
- Extreme pressure additives reduces clutch chatter

PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Density @ 15°C	ASTM D1298	kg/l	0.86
Viscosity @ 100°C	ASTM D445	cSt	15.7
Viscosity @ 40°C	ASTM D445	cSt	115
Viscosity Index (min)	ASTM D2270	-	144
Pour Point	ASTM D97	°C	-45
Flash Point	ASTM D92	°C	210

The values shown above are typical values at the date of publication, Petrocam Lubricants reserves the right to change these typical values without prior notice.

RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

PACKAGING

1, 5 and 20 litre plastic bottles & 208 litre drums