

BRAKE FLUID

DOT 3

HYDRAULIC BRAKE AND CLUTCH FLUID

A high-performance polyglycol brake fluid which optimises the benefits of superior boiling point and high vapour lock temperature throughout the entire braking system.

SPECIFICATIONS

SAEJ1703/4

ISO 4925

FMVSS 116



ENERGY
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa
TEL: +27 11 656 0466
EMAIL: info@petrocamlubricants.co.za

PETROCAM
— LUBRICANTS —

A Division of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za



APPLICATIONS

- Suitable for vehicles with ABS system, hydraulic clutch systems requiring conventional fluids
- Passenger cars, commercial road transport, off highway vehicles and tractors

KEY ADVANTAGE

- Compatible with all metals and rubber seals
- Extended fluid service life
- Excellent thermal and oxidation stability
- Maintains pH in alkaline environment

PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
FMVSS Grade			DOT 3
Color	Visual	-	Amber
Density @ 15°C	ASTM D1298	°C	1.0923
pH	ASTM D1287	-	9.0
Kinematic Viscosity @ 100°C	ASTM D445	cSt	2.2
Equilibrium Reflux Boiling Point	ASTM D1120	°C	240
Wet Equilibrium Reflux Boiling Point	ASTM D1120	°C	148
Pour Point	ASTM D97	°C	>-50

The values shown above are typical values at the date of publication, Petrocam Lubricants reserves the right to change these typical values without prior notice

RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

PACKING

250ml and 500ml plastic bottles