

ULTRA GREASE

EP-3

LITHIUM COMPLEX GREASE

A true multipurpose grease, formulated with “Extreme Pressure” additives, rust and oxidation inhibitors especially developed for operation under high temperature and severe shock loads.

SPECIFICATIONS

EP-3

APPLICATIONS

- Roller-bearings, wheel bearings, universal joints and chassis
- Industrial applications requiring a NLGI 3 grade “Extreme Pressure” grease
- Used in transport, agriculture and off-road vehicles

KEY ADVANTAGE

- Excellent all-round operating performance
- Enhanced extreme pressure properties
- Reduced wear under heavy or shock loading
- Resistance to water washout for equipment protection
- Protection against rust and corrosion
- Long service life

PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Soap/Thickener			Complex
NLGI Grade	ASTM D217	-	3
Color	Visual		Red
Appearance	Visual		Smooth
Operating Temperature range, °C	ASTM D217	°C	-30 to 140
Four ball weld load, daN	DIN 51 350-4		280-300
Penetration @ 25°C, 0.1 mm	ASTM D27	°C/mm	220-250
Dropping point, °C	IP 396/DIN ISO 2176	°C	≥190
Kinematic viscosity of the base oil @ 40°C, mm ² /s	ASTM D445	mm ² /s	165

The values shown above are typical values at the date of publication. Petrocam Lubricants reserves the right to change these typical values without prior notice.

RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

PACKAGING

500g and 1kg plastic bottles & 15kg buckets



ENERGY
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa
TEL: +27 11 656 0466
EMAIL: lubricants@petrocam.co.za

PETROCAM
— LUBRICANTS —

A Division of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za