

# BRAKE FLUID

## DOT 4

### HYDRAULIC BRAKE AND CLUTCH FLUID

A high-performance borate ester brake fluid which optimises the benefits of superior boiling point and high vapour lock temperature throughout the entire braking system.

#### SPECIFICATIONS

SAEJ1703/4

ISO 4925

FVMSS 116

#### APPLICATIONS

- Heavy-duty synthetic brake fluid suitable for vehicles with anti-skid ABS system, hydraulic clutch systems requiring conventional fluids
- Passenger cars, commercial road transport, off highway vehicles and tractors

#### KEY ADVANTAGE

- Compatible with all metals and rubber seals
- Extended fluid service life
- Contains antioxidants, metal deactivators and corrosion inhibitors
- Maintains pH in alkaline environment

#### PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
FMVSS Grade			DOT 4
Color	Visual	-	Amber
Density @ 15°C	ASTM D1298	°C	1.060
pH	ASTM D1287	-	9.0
Kinematic Viscosity @ 100°C	ASTM D445	cSt	2.2
Equilibrium Reflux Boiling Point	ASTM D1120	°C	260
Wet Equilibrium Reflux Boiling Point	ASTM D1120	°C	148
Pour Point	ASTM D97	°C	>-50

The values shown above are typical values at the date of publication. Petrocam Lubricants reserves the right to change these typical values without prior notice

#### RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

#### HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

#### PACKING

250ml and 500ml plastic bottles



ENERGY  
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa  
TEL: +27 11 656 0466  
EMAIL: info@petrocamlubricants.co.za

**PETROCAM**  
— LUBRICANTS —

A Division of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za