

# HYBRITE

## SAE 40

### CONVENTIONAL MOTOR OIL

A highly stable multi-functional conventional engine oil formulated with anti-wear and detergent technology for protection against engine wear and sludge build-up.

### SPECIFICATIONS

#### API SG/CF

### APPLICATIONS

- Mineral oil for conventional petrol, diesel and LPG engines
- Passenger car, light vans and trucks and farm equipment with or without turbo compressor
- Safe for use with catalytic converters
- Not suited for engines equipped with a Diesel or Gasoline Particle Filter

### KEY ADVANTAGE

- High viscosity index for better fuel and oil consumption
- Good detergency properties for anti corrosion and sludge control
- Anti wear technology reduce engine vibration and noise
- Excellent antioxidant and anti-foaming properties for long drain intervals
- Exceeds API service classifications and industry standards

### PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Density @ 15°C	ASTM D1298	kg/l	0.901
Viscosity @ 100°C	ASTM D445	cSt	14.5
Viscosity @ 40°C	ASTM D445	cSt	140
Viscosity Index (min)	ASTM D2270	-	103
Cold Crank Simulator	ASTM D5293	cP	-
Pour Point	ASTM D97	°C	-20
Flash Point	ASTM D92	°C	>220
Total Base Number (TBN)	ASTM D2896	KOH/g	12

The values shown above are typical values at the date of publication, Petrocam Lubricants reserves the right to change these typical values without prior notice.

### RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

### HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

### PACKAGING

1 and 5 litre plastic bottles



ENERGY  
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa  
TEL: +27 11 656 0466  
EMAIL: lubricants@petrocam.co.za

**PETROCAM**  
— LUBRICANTS —

A Division Of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za