

EXTREME

0W20

ADVANCED FULL SYNTHETIC MOTOR OIL

A premium full synthetic engine oil formulated for today's engines with high quality additives for high level protection, efficiency and stringent manufacturer's specifications.

SPECIFICATIONS

API SP/CF ACEA A1/B1

This product meets or exceeds the requirements of the latest API SP and ILSAC GF-6A industry specifications for engine oils, as well as the requirements of many major American and European engine manufacturers.



ENERGY
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa
TEL: +27 11 656 0466
EMAIL: lubricants@petrocam.co.za

PETROCAM
—LUBRICANTS—

A Division Of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za



APPLICATIONS

- Full synthetic engine oil for new generation petrol, diesel and LPG engines.
- Passenger cars and light vans with or without turbo compressor.
- Particularly suitable for turbo compressed, multi-valve and direct injection diesel engines.
- It is perfectly suited to engines with catalytic converters and all engines using lead free fuel or LPG.

KEY ADVANTAGE

- Ultra low viscosity for fuel efficiency
- Excellent cold start-up protection
- High resistance to shearing and friction
- Ultra-fast flowing formula
- Excellent engine cleanliness
- High and stable viscosity index resists breakdown
- High oxidation stability for sludge control
- Enhanced corrosion protection
- Helps to reduce oil aging resulting in long lasting protection

PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Density @ 15°C	ASTM D1298	kg/l	0.850
Viscosity @ 100°C	ASTM D445	cSt	7.5
Viscosity @ 40°C	ASTM D445	cSt	40
Viscosity Index (min)	ASTM D2270	-	158
Cold Crank Simulator	ASTM D5293	cP	<6,200 @ -35 °C
Pour Point	ASTM D97	°C	-45
Flash Point	ASTM D92	°C	>230
Total Base Number (TBN)	ASTM D2896	KOH/g	9

The values shown above are typical values at the date of publication, Petrocam Lubricants reserves the right to change these typical values without prior notice.

RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

PACKAGING

1 and 5 litre plastic bottles