

# ATF

## II-D

### MULTI VEHICLE

A synthetic blend multi-purpose automatic transmission fluid for use in automatic gear boxes and power steering systems formulated to enhance fluid performance, wear protection and transmission durability.

### SPECIFICATIONS DEXRON® II



### APPLICATIONS

- Transmission fluid for use in automatic gear boxes and power steering systems
- Automatic transmissions in more recent cars and light trucks

### KEY ADVANTAGE

- Excellent low temperature protection
- Compatible with wide range of seal materials
- Smooth transmission shift feel performance
- Excellent heat dissipation and foam suppression characteristics
- Outstanding friction durability performance over wide temperature

### PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Density @ 15°C	ASTM D1298	kg/l	0.870
Viscosity @ 100°C	ASTM D445	cSt	7.0
Viscosity @ 40°C	ASTM D445	cSt	37
Viscosity Index (min)	ASTM D2270	-	≥160
Brookfield Viscosity @ -40°C	ASTM D2983	cP	<50,000
Pour Point	ASTM D97	°C	-44
Flash Point	ASTM D92	°C	210

The values shown above are typical values at the date of publication. Petrocam Lubricants reserves the right to change these typical values without prior notice.

### RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

### HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

### PACKAGING

1 and 5 litre plastic bottles



ENERGY  
IN MOTION

6 Western Service Road, Sandton, 2052, South Africa  
TEL: +27 11 656 0466  
EMAIL: lubricants@petrocam.co.za

**PETROCAM**  
— LUBRICANTS —

A Division Of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za